https://fa.wikimarefat.ir/view/%D9%BE%D9%88%D8%AF%D9%85%D8%A7%D9%86:Documentation/config

پودمان:Documentation/config

.□□□□ □□□□□ [□□□□□□□□/Documentation/config:□□□□□□□](#) □□ □□□□□□□□ □□□□□□□ □□□□ □□□□□□□□

```
-------------------------------------------------------------------------------
-----------------------
--
--                               Configuration for Module:Documentation
--
-- Here you can set the values of the parameters and messages used in
Module:Documentation to
-- localise it to your wiki and your language. Unless specified otherwise,
values given here
-- should be string values.
-------------------------------------------------------------------------------
-----------------------

local cfg = {} -- Do not edit this line.

-------------------------------------------------------------------------------
-----------------------
-- Protection template configuration
-------------------------------------------------------------------------------
-----------------------

-- cfg['protection-reason-edit']
-- The protection reason for edit-protected templates to pass to
-- [[Module:Protection banner]].
cfg['protection-reason-edit'] = 'template'

--[[
-------------------------------------------------------------------------------
-----------------------
-- Sandbox notice configuration
--
-- On sandbox pages the module can display a template notifying users that
the current page is a
-- sandbox, and the location of test cases pages, etc. The module decides
whether the page is a
-- sandbox or not based on the value of cfg['sandbox-subpage']. The following
settings configure the
-- messages that the notices contains.
-------------------------------------------------------------------------------
-----------------------
--]]
```

```
-- cfg['sandbox-notice-image']
-- The image displayed in the sandbox notice.
cfg['sandbox-notice-image'] = '[[پرونده:Sandbox.svg|50px|پیوند|=جایگزین=]]'

--[[
-- cfg['sandbox-notice-pagetype-template']
-- cfg['sandbox-notice-pagetype-module']
-- cfg['sandbox-notice-pagetype-other']
-- The page type of the sandbox page. The message that is displayed depends
on the current subject
-- namespace. This message is used in either cfg['sandbox-notice-blurb'] or
-- cfg['sandbox-notice-diff-blurb'].
--]]
cfg['sandbox-notice-pagetype-template'] = 'صفحهٔ [[ویکی‌پدیا:تمرین و نمونه‌های
آزمایشی الگو|تمرین الگو]]'
cfg['sandbox-notice-pagetype-module'] = 'صفحهٔ [[ویکی‌پدیا:تمرین و نمونه‌های
آزمایشی الگو|تمرین پودمان]]'
cfg['sandbox-notice-pagetype-other'] = 'صفحهٔ تمرین'

--[[
-- cfg['sandbox-notice-blurb']
-- cfg['sandbox-notice-diff-blurb']
-- cfg['sandbox-notice-diff-display']
-- Either cfg['sandbox-notice-blurb'] or cfg['sandbox-notice-diff-blurb'] is
the opening sentence
-- of the sandbox notice. The latter has a diff link, but the former does
not. $1 is the page
-- type, which is either cfg['sandbox-notice-pagetype-template'],
-- cfg['sandbox-notice-pagetype-module'] or cfg['sandbox-notice-pagetype-
other'] depending what
-- namespace we are in. $2 is a link to the main template page, and $3 is a
diff link between
-- the sandbox and the main template. The display value of the diff link is
set by
-- cfg['sandbox-notice-compare-link-display'].
--]]
cfg['sandbox-notice-blurb'] = 'این $1 برای $2 است.'
cfg['sandbox-notice-diff-blurb'] = 'این $1 برای $2 است ($3).'
cfg['sandbox-notice-compare-link-display'] = 'تفاوت'

--[[
-- cfg['sandbox-notice-testcases-blurb']
-- cfg['sandbox-notice-testcases-link-display']
-- cfg['sandbox-notice-testcases-run-blurb']
-- cfg['sandbox-notice-testcases-run-link-display']
-- cfg['sandbox-notice-testcases-blurb'] is a sentence notifying the user
that there is a test cases page
-- corresponding to this sandbox that they can edit. $1 is a link to the test
cases page.
-- cfg['sandbox-notice-testcases-link-display'] is the display value for that
link.
```

```
-- cfg['sandbox-notice-testcases-run-blurb'] is a sentence notifying the user
that there is a test cases page
-- corresponding to this sandbox that they can edit, along with a link to run
it. $1 is a link to the test
-- cases page, and $2 is a link to the page to run it.
-- cfg['sandbox-notice-testcases-run-link-display'] is the display value for
the link to run the test
-- cases.
--]]
cfg['sandbox-notice-testcases-blurb'] = 'همچنین زیرصفحه همنشین برای $1 را
ببینید.'
cfg['sandbox-notice-testcases-link-display'] = 'نمونه‌های آزمایشی'
cfg['sandbox-notice-testcases-run-blurb'] = 'همچنین زیرصفحه همنشین برای $1
را ببینید ($2).'
cfg['sandbox-notice-testcases-run-link-display'] = 'اجرا'

-- cfg['sandbox-category']
-- A category to add to all template sandboxes.
cfg['sandbox-category'] = 'صفحه تمرین الگوها'

------------------------------------------------------------------------------
------------------------
-- Start box configuration
------------------------------------------------------------------------------
------------------------

-- cfg['documentation-icon-wikitext']
-- The wikitext for the icon shown at the top of the template.
cfg['documentation-icon-wikitext'] = '[[پرونده:Test Template Info-Icon -
Version (2).svg|50px|جایگزین=|پیوند=]]'

-- cfg['template-namespace-heading']
-- The heading shown in the template namespace.
cfg['template-namespace-heading'] = 'توضیحات الگو'

-- cfg['module-namespace-heading']
-- The heading shown in the module namespace.
cfg['module-namespace-heading'] = 'توضیحات پودمان'

-- cfg['file-namespace-heading']
-- The heading shown in the file namespace.
cfg['file-namespace-heading'] = 'خلاصه'

-- cfg['other-namespaces-heading']
-- The heading shown in other namespaces.
cfg['other-namespaces-heading'] = 'توضیحات'

-- cfg['view-link-display']
-- The text to display for "view" links.
cfg['view-link-display'] = 'نمایش'
```

```
-- cfg['edit-link-display']
-- The text to display for "edit" links.
cfg['edit-link-display'] = 'ویرایش'

-- cfg['history-link-display']
-- The text to display for "history" links.
cfg['history-link-display'] = 'تاریخچه'

-- cfg['purge-link-display']
-- The text to display for "purge" links.
cfg['purge-link-display'] = 'پاکسازی'

-- cfg['create-link-display']
-- The text to display for "create" links.
cfg['create-link-display'] = 'ایجاد'

------------------------------------------------------------------------------
------------------------
-- Link box (end box) configuration
------------------------------------------------------------------------------
------------------------

-- cfg['transcluded-from-blurb']
-- Notice displayed when the docs are transcluded from another page. $1 is a
wikilink to that page.
cfg['transcluded-from-blurb'] = '[[ویکی‌پدیا:مستندسازی الگوها|توضیحات]] بالا
است 1$ از [[ویکی‌پدیا:تراگنجانش|تراگنجانده‌شده]].'

--[[
-- cfg['create-module-doc-blurb']
-- Notice displayed in the module namespace when the documentation subpage
does not exist.
-- $1 is a link to create the documentation page with the preload
cfg['module-preload'] and the
-- display cfg['create-link-display'].
--]]
cfg['create-module-doc-blurb'] = 'در صورت تمایل می‌توانید یک صفحهٔ توضیحات
کنید 1$ [[ویکی‌پدیا:لوآ|پودمان اسکریبونتو]] برای این.'

------------------------------------------------------------------------------
------------------------
-- Experiment blurb configuration
------------------------------------------------------------------------------
------------------------

--[[
-- cfg['experiment-blurb-template']
-- cfg['experiment-blurb-module']
-- The experiment blurb is the text inviting editors to experiment in sandbox
and test cases pages.
-- It is only shown in the template and module namespaces. With the default
```

```
English settings, it
-- might look like this:
--
-- Editors can experiment in this template's sandbox (edit | diff) and
testcases (edit) pages.
--
-- In this example, "sandbox", "edit", "diff", "testcases", and "edit" would
all be links.
--
-- There are two versions, cfg['experiment-blurb-template'] and
cfg['experiment-blurb-module'], depending
-- on what namespace we are in.
--
-- Parameters:
--
-- $1 is a link to the sandbox page. If the sandbox exists, it is in the
following format:
--
--     cfg['sandbox-link-display'] (cfg['sandbox-edit-link-display'] |
cfg['compare-link-display'])
--
-- If the sandbox doesn't exist, it is in the format:
--
--     cfg['sandbox-link-display'] (cfg['sandbox-create-link-display'] |
cfg['mirror-link-display'])
--
-- The link for cfg['sandbox-create-link-display'] link preloads the page
with cfg['template-sandbox-preload']
-- or cfg['module-sandbox-preload'], depending on the current namespace. The
link for cfg['mirror-link-display']
-- loads a default edit summary of cfg['mirror-edit-summary'].
--
-- $2 is a link to the test cases page. If the test cases page exists, it is
in the following format:
--
--     cfg['testcases-link-display'] (cfg['testcases-edit-link-display'] |
cfg['testcases-run-link-display'])
--
-- If the test cases page doesn't exist, it is in the format:
--
--     cfg['testcases-link-display'] (cfg['testcases-create-link-display'])
--
-- If the test cases page doesn't exist, the link for cfg['testcases-create-
link-display'] preloads the
-- page with cfg['template-testcases-preload'] or cfg['module-testcases-
preload'], depending on the current
-- namespace.
--]]
cfg['experiment-blurb-template'] = "ویرایشگران می‌توانند در صفحات $1 و $2 این
الگو را آزمایش کنند."
cfg['experiment-blurb-module'] = "ویرایشگران می‌توانند در صفحات $1 و $2 این
```

".پودمان را آزمایش کنند

```
------------------------------------------------------------------------------
----------------------
-- Sandbox link configuration
------------------------------------------------------------------------------
----------------------

-- cfg['sandbox-subpage']
-- The name of the template subpage typically used for sandboxes.
cfg['sandbox-subpage'] = 'تمرین'

-- cfg['template-sandbox-preload']
-- Preload file for template sandbox pages.
cfg['template-sandbox-preload'] = 'الگو:توضیحات/پیش‌بارگیری-تمرین'

-- cfg['module-sandbox-preload']
-- Preload file for Lua module sandbox pages.
cfg['module-sandbox-preload'] = 'الگو:توضیحات/پیش‌بارگیری-تمرین-پودمان'

-- cfg['sandbox-link-display']
-- The text to display for "sandbox" links.
cfg['sandbox-link-display'] = 'تمرین'

-- cfg['sandbox-edit-link-display']
-- The text to display for sandbox "edit" links.
cfg['sandbox-edit-link-display'] = 'ویرایش'

-- cfg['sandbox-create-link-display']
-- The text to display for sandbox "create" links.
cfg['sandbox-create-link-display'] = 'ایجاد'

-- cfg['compare-link-display']
-- The text to display for "compare" links.
cfg['compare-link-display'] = 'تفاوت'

-- cfg['mirror-edit-summary']
-- The default edit summary to use when a user clicks the "mirror" link. $1
is a wikilink to the
-- template page.
cfg['mirror-edit-summary'] = 'نسخهٔ تمرینی $1 را ایجاد کنید'

-- cfg['mirror-link-display']
-- The text to display for "mirror" links.
cfg['mirror-link-display'] = 'آینه'

-- cfg['mirror-link-preload']
-- The page to preload when a user clicks the "mirror" link.
cfg['mirror-link-preload'] = 'الگو:توضیحات/آینه'

------------------------------------------------------------------------------
```

```
-----------------------
-- Test cases link configuration
-------------------------------------------------------------------------------
-----------------------

-- cfg['testcases-subpage']
-- The name of the template subpage typically used for test cases.
cfg['testcases-subpage'] = 'آزمایشی'

-- cfg['template-testcases-preload']
-- Preload file for template test cases pages.
cfg['template-testcases-preload'] = 'الگو:توضیحات/پیش‌بارگیری-آزمایشی'

-- cfg['module-testcases-preload']
-- Preload file for Lua module test cases pages.
cfg['module-testcases-preload'] = 'الگو:توضیحات/پیش‌بارگیری-آزمایشی-پودمان'

-- cfg['testcases-link-display']
-- The text to display for "testcases" links.
cfg['testcases-link-display'] = 'آزمایشی'

-- cfg['testcases-edit-link-display']
-- The text to display for test cases "edit" links.
cfg['testcases-edit-link-display'] = 'ویرایش'

-- cfg['testcases-run-link-display']
-- The text to display for test cases "run" links.
cfg['testcases-run-link-display'] = 'اجرا'

-- cfg['testcases-create-link-display']
-- The text to display for test cases "create" links.
cfg['testcases-create-link-display'] = 'ایجاد'

-------------------------------------------------------------------------------
-----------------------
-- Add categories blurb configuration
-------------------------------------------------------------------------------
-----------------------

--[[
-- cfg['add-categories-blurb']
-- Text to direct users to add categories to the /doc subpage. Not used if
the "content" or
-- "docname fed" arguments are set, as then it is not clear where to add the
categories. $1 is a
-- link to the /doc subpage with a display value of cfg['doc-link-display'].
--]]
cfg['add-categories-blurb'] = 'لطفاً رده‌ها را به زیرصفحهٔ $1 بیفزایید.'

-- cfg['doc-link-display']
-- The text to display when linking to the /doc subpage.
```

```
cfg['doc-link-display'] = '/توضیحات'

-------------------------------------------------------------------------------
-- Subpages link configuration
-------------------------------------------------------------------------------

--[[
-- cfg['subpages-blurb']
-- The "Subpages of this template" blurb. $1 is a link to the main template's
subpages with a
-- display value of cfg['subpages-link-display']. In the English version this
blurb is simply
-- the link followed by a period, and the link display provides the actual
text.
--]]
cfg['subpages-blurb'] = '$1.'

--[[
-- cfg['subpages-link-display']
-- The text to display for the "subpages of this page" link. $1 is
cfg['template-pagetype'],
-- cfg['module-pagetype'] or cfg['default-pagetype'], depending on whether
the current page is in
-- the template namespace, the module namespace, or another namespace.
--]]
cfg['subpages-link-display'] = 'زیرصفحه‌های این $1'

-- cfg['template-pagetype']
-- The pagetype to display for template pages.
cfg['template-pagetype'] = 'الگو'

-- cfg['module-pagetype']
-- The pagetype to display for Lua module pages.
cfg['module-pagetype'] = 'پودمان'

-- cfg['default-pagetype']
-- The pagetype to display for pages other than templates or Lua modules.
cfg['default-pagetype'] = 'صفحه'

-------------------------------------------------------------------------------
-- Doc link configuration
-------------------------------------------------------------------------------

-- cfg['doc-subpage']
-- The name of the subpage typically used for documentation pages.
cfg['doc-subpage'] = 'توضیحات'
```

```
-- cfg['file-docpage-preload']
-- Preload file for documentation page in the file namespace.
cfg['file-docpage-preload'] = 'الگو:توضیحات/پیش‌بارگیری-فضای-پرونده'

-- cfg['docpage-preload']
-- Preload file for template documentation pages in all namespaces.
cfg['docpage-preload'] = 'الگو:توضیحات/پیش‌بارگیری'

-- cfg['module-preload']
-- Preload file for Lua module documentation pages.
cfg['module-preload'] = 'الگو:توضیحات/پیش‌بارگیری-توضیحات-پودمان'

--------------------------------------------------------------------------------
----------------------
-- HTML and CSS configuration
--------------------------------------------------------------------------------
----------------------

-- cfg['templatestyles']
-- The name of the TemplateStyles page where CSS is kept.
-- Sandbox CSS will be at Module:Documentation/sandbox/styles.css when
needed.
cfg['templatestyles'] = 'پودمان:Documentation/styles.css'

-- cfg['container']
-- Class which can be used to set flex or grid CSS on the
-- two child divs documentation and documentation-metadata
cfg['container'] = 'documentation-container'

-- cfg['main-div-classes']
-- Classes added to the main HTML "div" tag.
cfg['main-div-classes'] = 'documentation'

-- cfg['main-div-heading-class']
-- Class for the main heading for templates and modules and assoc. talk
spaces
cfg['main-div-heading-class'] = 'documentation-heading'

-- cfg['start-box-class']
-- Class for the start box
cfg['start-box-class'] = 'documentation-startbox'

-- cfg['start-box-link-classes']
-- Classes used for the [view][edit][history] or [create] links in the start
box.
-- mw-editsection-like is per [[Wikipedia:Village pump (technical)/Archive
117]]
cfg['start-box-link-classes'] = 'mw-editsection-like plainlinks'

-- cfg['end-box-class']
-- Class for the end box.
```

```
cfg['end-box-class'] = 'documentation-metadata'

-- cfg['end-box-plainlinks']
-- Plainlinks
cfg['end-box-plainlinks'] = 'plainlinks'

-- cfg['toolbar-class']
-- Class added for toolbar links.
cfg['toolbar-class'] = 'documentation-toolbar'

-- cfg['clear']
-- Just used to clear things.
cfg['clear'] = 'documentation-clear'


------------------------------------------------------------------------
------------------------
-- Tracking category configuration
------------------------------------------------------------------------
------------------------

-- cfg['display-strange-usage-category']
-- Set to true to enable output of cfg['strange-usage-category'] if the
module is used on a /doc subpage
-- or a /testcases subpage. This should be a boolean value (either true or
false).
cfg['display-strange-usage-category'] = true

-- cfg['strange-usage-category']
-- Category to output if cfg['display-strange-usage-category'] is set to true
and the module is used on a
-- /doc subpage or a /testcases subpage.
cfg['strange-usage-category'] = 'توضیحات «صفحات ویکی‌پدیا با کاربرد عجیب»'

--[[
------------------------------------------------------------------------
------------------------
-- End configuration
--
-- Don't edit anything below this line.
------------------------------------------------------------------------
------------------------
--]]

return cfg
```